conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Color:

Demotec FuturaPad Special glue colorless.

UFI: T8KV-3Y8Y-EW04-6AYE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Special glue belonging to the Demotec FuturaPad system for bovine clawcare.

1.3. Details of the supplier of the safety data sheet

Demotec Demel e.K. Company name:

Distributed by: Shoof International Ltd

New Zealand:

224 Laurent Road, Cambridge 3493, New Zealand

www.shoof.co.nz

Australia:

1 International Square, Tullamarine VIC 3043, Australia

Emergency Contact: NZ:0800 POISON (0800 764 766) AU: 13 11 26

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Produkt definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 **STOT SE 3, H335**

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2. Label elements
Signal word: Warning

Hazard pictogram:



Hazard statements

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

Precautionary statements

Prevention: P280 - Wear protective gloves. Wear eye or face protection.

P271 - Use only outdoors or in a well-ventilated area.

P261 - Avoid breathing vapor.

P264 - Wash thoroughly after handling.

P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Response:

P362 + P364 - Take off contaminated clothing and wash it before reuse.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 2 of 13

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage: P405 - Store locked up.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal: P501 - Dispose of waste according to applicable legislation.

Hazardous ingredients: ethyl 2-cyanoacrylate

Supplemental label

elements: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles: Not applicable

2.3. Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII:

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification:

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures: Mixture

Product/Ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M- factors and ATEs	Туре
ethyl 2- cyanoacrylate	REACH #: 01-2119527766-29 EF: 230-391-5 CAS: 7085-85-0 Index: 607-236-00-9	≥90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, 335 See Section 16 for the full text of the H statements declared above.	STOT SE 3, H335: C ≥ 10%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

Inhalation:

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for

and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected

that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 3 of 13

airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of

decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to

rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an

unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders:

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed

person may need to be kept under medical surveillance for 48 hours.

Specific treatments:

No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance

or mixture: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous

combustion products: Decomposition products may include the following materials:

carbon dioxide, carbon monoxide, nitrogen oxides

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 4 of 13

5.3. Advice for firefighters

Special protective actions for fire-fighters:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment

for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate

surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate

personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in

Section 8 on suitable and unsuitable materials. See also the information in "For non-

emergency personnel".

6.2. Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3. Methods and materials for containment and cleaning up:

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6.4. Reference to other sections:

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1. Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid

contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not

reuse container.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 5 of 13

7.2. Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3. Specific end use(s)

Recommendations: Industrial sector specific Not available.

solutions: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1.Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ethyl 2-cyanoacrylate	DFG MAC-values list (Germany, 10/2021). [Cyanides]
	Absorbed through skin.
	TWA: 2 mg/m³, (as CN) 8 hours. Form: inhalable fraction
	PEAK: 2 mg/m³, (as CN), 4 times per shift, 15 minutes.
	Form: inhalable fraction

Recommended monitoring procedures:

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredients	Type	Exposure	Value	Population	Effects
name					
ethyl 2-cyanoacrylate	DNEL	Long term Inhalation	9.25 mg/m ³	General population	Local
	DNEL	Long term Inhalation	9.25 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	9.25 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	9.25 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	9.25 mg/m ³	General population	Local
	DNEL	Short term Inhalation	9.25 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	9.25 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	9.25 mg/m ³	Workers	Systemic

PNEC's

No PNECs available.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 6 of 13

8.2. Exposure controls

Appropriate engineering

controls:

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory

limits.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove

manufacturers. Recommended: 1 - 4 hours (breakthrough time): nitrile rubber; 4 - 8 hours

(breakthrough time): Viton®/butyl rubber

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapor (Type AX) and particulate filter

Environmental

exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

<u>Appearance</u>

Physical state: Liquid. Color: Colorless. Odor: Characteristic. Odr threshold: Not available.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 7 of 13

Melting point/freezing point:

Inititial boiling point and

boiling range:

Flammability:

Not available. 150°C (302°F)

Not available.

Upper/lower flammability or

Explosive limits: Not available.

Flash point: Closed cup: 87°C (188.6°F)

Aut-ignition temperature: >500°C (>932°F) Not available. Decomposition temperature: Not applicable. pH: Not available. Viscosity: Solubility(ies): Not available. Solubility in water: Not applicable.

Partition coefficient:

n-octanol/water: Not applicable.

Vapor pressure:

Ingredient name	V	Vapor Pressure at 20°C			oor pressure at 5	0°C
	mm Hg	kPa	Method	mm Hg	kPa	Method
Ethyl-2-cynacrylat	0.16	0.021	EU A.4			

Relative density: Not available.

Density: 1 g/cm³ [20°C (68°F)]

Not available. Vapor density: Explosive properties: Not available. Oxidizing propoerties: Not available.

Particle characteristics

Median particle size: Not applicable.

> 100°C Fire point: SADT: Not available. SAPT: Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity:

No specific test data related to reactivity available for this product or its ingredients.

10.2. Chemical stability

The product is stable.

10.3. Possibility of hazardous reactions

Hazardous reactions or instability may occur under certain conditions of storage or use.

10.4. Conditions to avoid

No specific data.

10.5. Incompatible materials

No specific data.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 8 of 13

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethyl 2-cyanoacrylate	LC50 Inhalation Vapor	Rat	21110mg/m ³	1 hours

Conclusion /

Summary: Not available.

Acute toxicity estimates

	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient	Result	Species	Score	Exposure	Obersvation
name					
ethyl 2-cyanoacrylate	Skin – Mild irritant	Rabbit	-	0,5 g	-
	Skin – Mild irritant	Rabbit	-	24 hours 500uL	-

Conclusion/Summary:

Skin: Irritating to skin. Eyes: Irritating to eyes.

Respiratory: May cause respiratory irritation.

Sensitization

Conclusion/Summary:

Not available.

Mutagenicity

Conclusion/Summary:

Not available.

Carcinogenicity

Conclusion/Summary:

Not available.

Reproductive toxicity

Conclusion/Summary:

Not available.

Teratogenicity

Conclusion/Summary:

Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethyl 2-cyanoacrylate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 9 of 13

Information on the likely

routes of exposure: Not available.

Potentional acute health effects

Eye contact: Causes serious eye irritation. Inhalation: May cause respiratory irritation.

Skin contact: Causes skin irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects: Not available.

Potential delayed

effects: Not available.

Long term exposure

Potential immediate effects: Not available.

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary:

Not available.

General:

Carcinogenicity:

Mutagenicity:

No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 10 of 13

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary:

Not available.

12.2 Persistence and degradability

Conclusion/Summary:

Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition

coefficient (K_{oc}): Not available.

Mobility: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Disposal of

this product, solutions and any by-products should at all times comply with the

requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless

fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

Packaging

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Waste

packaging should be recycled. Incineration or landfill should only be considered when

recycling is not feasible.

15 01 10* packaging containing residues of or contaminated by hazardous substances	Type of packaging	European waste catalogue (EWC)
	15 01 10*	packaging containing residues of or contaminated by hazardous substances

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 11 of 13

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packaging group	-	-	-
14.5 Environmental hazards	No. Not available.	No. Not available.	No.

Additional information

IATA:

Quantity limitation Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y964. **Special provisions** A27

14.6. Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments:

Not available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Restrictions on Manufacture, Marketing and Use

Country Product name Conc. Designation Usage

Other EU regulations

Industrial emissions (integrated pollution prevention and control) -

Air: Listed

Industrial emissions (integrated pollution prevention and control) -

Water: Listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 12 of 13

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Storage class (TRGS 510): 10

Hazardous incident ordinance This product is not controlled under the Germany Hazardous Incident Ordinance

Hazard class for water: 1

Technical instruction on air quality control:

TA-Luft Nummer 5.2.5:96-100%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protokoll

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia: All components are listed or exempted.
Canada: All components are listed or exempted.
China: All components are listed or exempted.

Eurasian

Economic Union:

Russian Federation inventory: Not determined.

Japan: Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

New Zealand: All components are listed or exempted.

Philippines: All components are listed or exempted.

Republic of Korea:

All components are listed or exempted.

Taiwan: Not determined.

Thailand: All components are listed or exempted.

Turkey: Not determined.

United States: All components are active of exempted. **Viet Nam:** All components are active of exempted.

15.2. Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

conforms to Regulation (EC) No. 1907/2006

Demotec FuturaPad Special glue

Revision date: 23.02.2023 Page 13 of 13

SECTION 16: Other information

Abbreviations and acronyms:

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.	٦
H319	Causes serious eye irritation.	ĺ
H335	May cause respiratory irritation.	Ì

Full text of classifications [CLP/GHS]

Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
	Category 3

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)