

Udder Singe Gas Refill 650ml

Changing the Cartridge – Instructions

Always refer to the appliance instructions before changing the gas cartridge. Always change or fit gas cylinders outdoors and away from other people and sources of heat. Keeping the gas cylinder upright, carefully screw the cylinder into the blowlamp handle burner or appliance assembly by rotating in a clockwise direction. Be careful to not cross-thread the gas cylinder. Should this occur, do not use the product and replace cylinder. A cross-threaded gas cylinder will not provide a sufficient seal between the O-ring and valve on top of the gas cylinder and could be dangerous. Do not over-tighten the cylinder as this may damage the gas cylinder valve and could be dangerous.

The cylinder should be attached by hand only. Do not use tools to attach the cylinder. It should be screwed in firmly but not using excessive force. Please read notes on checking for leaks after attaching. Warning: whilst connecting the gas cylinder, a small amount of gas will be released before the cylinder is screwed in fully against the O-ring seal. It is normal for this to happen so always fit gas cylinder outdoors, away from other people and sources of heat.

Before lighting the appliance, you must check for gas leaks around the connection point (cylinder to handle/head assembly). Do not use the appliance if you suspect there may be some gas leakage at this point. Immerse the appliance in soapy water. Any leaks will be seen as bubbles. If you are unable to find a remedy for leaking gas, return the product to your retailer. Never use a flame to check for leaks.

Always ensure the flame is extinguished before removing the gas cylinder. Always wait for the appliance to cool down to room temperature before removing or fitting gas cylinder. To remove the gas cylinder, rotate it in an anti-clockwise direction. Whilst unscrewing the cylinder, a small amount of gas will be released between the O-ring seal and the cylinder. This is normal. Always remove cylinders outdoors.

